

MODIFICATION OF AUSTENITIC CAST
IRON (NI-RESIST) WITH HIGH MANGANESE
CONTENT BY USING HEAT TREATMENT

KHAIRUL MUZAFAR BIN AHMAD

Master of Science

UNIVERSITI MALAYSIA PAHANG



SUPERVISOR'S DECLARATION

I/We* hereby declare that I/We* have checked this thesis/project* and in my/our* opinion, this thesis/project* is adequate in terms of scope and quality for the award of the degree of *Doctor of Philosophy/ Master of Engineering/ Master of Science in

(Supervisor's Signature)

Full Name :

Position :

Date :

(Co-supervisor's Signature)

Full Name :

Position :

Date :



STUDENT'S DECLARATION

I hereby declare that the work in this thesis is based on my original work except for quotations and citations which have been duly acknowledged. I also declare that it has not been previously or concurrently submitted for any other degree at Universiti Malaysia Pahang or any other institutions.

(Student's Signature)

Full Name : KHAIRUL MUZAFAR BIN AHMAD

ID Number : MMM 14014

Date : 28 June 2017

MODIFICATION OF AUSTENITIC CAST IRON (NI-RESIST) WITH HIGH
MANGANESE CONTENT BY USING HEAT TREATMENT

KHAIRUL MUZAFAR BIN AHMAD

Thesis submitted in fulfillment of the requirements
for the award of the degree of
Master of Science

Faculty of Mechanical Engineering
UNIVERSITI MALAYSIA PAHANG

OCTOBER 2017

ACKNOWLEDGEMENTS

In the name of Allah S.W.T, the most gracious and merciful who had given me the strength and ability to complete this master thesis project. All perfect praise belongs to Allah S.W.T. Lord of the universe. May this blessing belong to the Prophet Muhammad S.A.W. and member of family and companion. Such wonderful and invaluable experiences in this period have made my life richer and stronger. I have completed my research entitled “Modification Of Austenitic Cast Iron (Ni-Resist) With Higher Manganese Content By Using Annealing Process” and graduated in Master of Engineering (Mechanical).

For this golden opportunity, I would like to express my deep regards, sincere gratitude and appreciation to my Supervisor Dr. Ir. Mohd Rashidi bin Maarof and Co-supervisor Prof Madya Dr. Mahadzir bin Ishak for his understanding, persistence constructive and professional ways in assisting and giving his invaluable advice and from the beginning to final stage. Without his untiring efforts meticulous attention and guidance, this study could not have been complete.

This acknowledgment would not be complete without mentioning my lovely family, especially my mother, my father, my brother and my sister that gives a patience and moral support.

My deep appreciation also goes to all staffs in the workshop, lecturers and my friend from my beloved faculty, Faculty of Mechanical Engineering and my roommates, your warmth, generosity, and friendship will always remain in my heart, as we crossed path during this period, as the friendship that we build. Not forgetting, University Malaysia Pahang (UMP) and Government of Malaysia for supporting and contributing this research program. Thank you for developing the out of me.

ABSTRAK

Besi Tuangan Austenitic (Ni-resist) digunakan secara meluas dalam industri kimia dan loji kuasa, automotif dan industri minyak dan gas. Bahan ini menawarkan ketidakstabilan sifat yang luar biasa pada suhu yang cukup tinggi dan ketahanan terhadap pengaratan dan hakisan seperti yang dituntut oleh industri. Struktur mikro Austenitic dalam Ni-melawan wujud kerana pengaruh nikel sebagai pemangkin austenitic matrik yang utama. Walau bagaimanapun, menggunakan nikel sebagai aloi tambahan utama untuk pengeluaran Ni-menolak Alloy adalah mahal kerana mempunyai harga yang tidak stabil. Oleh itu, menggunakan mangan sebagai pengganti nikel atau campuran keduanya untuk memangkin matriks austenit adalah pilihan yang boleh diambil kira dalam mengurangkan jumlah kos pemprosesan. Oleh itu, kajian ini bertujuan untuk meneroka kemungkinan untuk mengurangkan penggunaan nikel dengan penggantian mangan untuk menjana struktur austenit Ni-resist. Selain itu, penyiasatan mengenai kesan sifat-sifat ke arah perubahan Ni-resistif (Mn-Ni-resist) sebelum dan selepas rawatan haba adalah menarik untuk dikaji. Bahan besi austenit mangan yang lebih tinggi dengan kandungan nikel yang dikurangkan (Mn-Ni-resist) dihasilkan dengan kandungan mangan 9 wt%, 10 wt%, 11wt% dan 12wt% menggunakan blok Y berdasarkan piawaian ASTM A436 dengan menggunakan acuan pasir hijau. Sampel kemudian dipanaskan pada suhu 700°C, 800 °C, 900 °C, dan 1000 °C selama 3 jam sebelum perlahan-lahan didinginkan ke suhu bilik dalam suhu relau. Hubungan kompleks antara pembangunan mikrostruktur pemejalan dan membina pemisahan mikro disebabkan peningkatan Mn wt% dalam Mn-Ni-resist diperoleh dengan menggunakan analisis lengkung haba pendinginan dan dibantu dengan pemerhatian mikroskopik dan ujian mekanik. Eksperimen menggambarkan pencirian mikrosegregasi dalam Mn-Ni-resist telah dibuat menggunakan kiraan mikroanalisis di sepanjang mikrostruktur. Hasilnya menunjukkan bahawa penambahan mangan dan rawatan haba mempengaruhi struktur mikro dan sifat mekanik. Lenkung penyejukan menurun dan morfologi austenit lengan dendrite dilihat memendek sebagai peningkatan Mn wt%. Kemudian, kekuatannya berkurangan dan lebih rendah berbanding dengan besi tuang konvensional. Pemerhatian mikrostruktur menunjukkan bahawa Mn-Ni-resist terdiri daripada serpihan grafit yang tertanam dalam matriks austenitik dan karbida terkumpul di dalam bingkai grafit yang berbentuk roset dimana dikenali juga sebagai rantau membekukan terlambat(LTF). Suhu *annealed* yang lebih tinggi pada Mn-Ni-resist telah berjaya mengurangkan pembentukan karbida dan sedikit meningkatkan kekuatan tegangan. Suhu *annealed* yang lebih tinggi menunjukkan karbida diubah menjadi saiz yang lebih kecil dan menyebar melalui struktur matriks austenit. Saiz karbida menurun dengan peningkatan suhu *annealed* seperti yang diperhatikan dalam struktur mikro. Sebaliknya kekerasan berkurangan apabila suhu annealed bertambah.

ABSTRACT

Austenitic cast iron broadly used in chemical and power plant, automotive and oil and gas industry. This material offers outstanding properties instability at a moderately high temperature and resistance to corrosion and wear which demanded by the industry. Austenitic microstructure in Ni-resist exists due to the influence of nickel as prime austenitic matrix promoter. However, using nickel as prime alloy addition for the production of Ni-resist Alloy is expensive due to its unstable prices. So, employing manganese as nickel replacement or mixing with for austenitic matrix promoter is an option that may reduce total processing cost. Therefore, the present study aims to explore the possibility to reduce nickel consumption by manganese substitution to generate the austenitic structure of Ni-resist. Furthermore, an investigation on the effect of the properties towards modified Ni-resist (Mn-Ni-resist) before and after heat treatment is appealing. Higher manganese austenitic cast iron with reduced nickel content (Mn-Ni-resist) was produced with manganese content nine wt%, ten wt%, 11 wt% and 12 wt% through Y-block according to ASTM A436 by using a green sand mold. Samples were then annealed at 700°C, 800 °C, 900 °C, and 1000°C for 3 hours before slowly cooled to room temperature in furnace temperature. The complex relationship between the development of the solidification microstructures and build up of micro-segregation due to increasing Mn wt% in Mn-Ni-resist was obtained by using cooling curve thermal analysis and complemented by microscopic observation and mechanical properties. Experimental describe the characterization of microsegregation in Mn-Ni-resist was made using point counting microanalysis along the microstructure. The result showed that manganese addition and heat treatment affect the microstructure and mechanical properties. Solidification cooling curve decreased, and the morphology of austenite dendrite arm shortened as the Mn wt% increased. Then, the strength reduced and more inferior compared to conventional cast iron. Microstructure observations revealed that Mn-Ni-resist consists of flake graphite embedded in the austenitic matrix and the accumulative of carbide at the frame of the rosette flake graphite and also known as late to freeze region (LTF). Higher annealing temperature on the Mn-Ni-resist has successfully reduced carbide formation and slightly increases tensile strength. The higher annealing temperature shows carbide altered into a smaller size and disperses through the austenitic matrix structure. The size of carbide decreased with increasing annealing temperature as observed in the microstructure. On the other hand, hardness diminished as the annealing temperature increases.

TABLE OF CONTENT

DECLARATION

TITLE PAGE

ACKNOWLEDGEMENTS **ii**

ABSTRAK **iii**

ABSTRACT **iv**

TABLE OF CONTENT **v**

LIST OF TABLES **ix**

LIST OF FIGURES **x**

LIST OF SYMBOLS **xiii**

LIST OF ABBREVIATIONS **xiv**

CHAPTER 1 INTRODUCTION **1**

1.1 Introduction 1

1.2 Problem Statement 4

1.3 Objectives of the Study 5

1.4 Significant of Study 5

1.5 Scope of the Study 6

1.5.1 Phase 01 6

1.5.2 Phase 02 6

1.5.3 Phase 03 6

1.5.4 Phase 04 6

CHAPTER 2 LITERATURE REVIEW	8
2.1 Introduction	8
2.2 Cast Iron	9
2.3 Austenitic Cast Iron	13
2.4 Properties of Austenitic cast iron	14
2.5 Solidification of Austenitic Cast Iron	16
2.5.1 Matrix Formation	16
2.5.2 Segregation	22
2.6 Inoculation	24
2.7 Austenitic Promoter	28
2.7.1 Manganese	29
2.7.2 Copper	32
2.8 Thermal analysis	32
2.9 Heat Treatment of Austenitic Cast Iron	37
2.10 Summary	38
 CHAPTER 3 METHODOLOGY	 42
3.1 Introduction	42
3.2 Flow Chart	42
3.3 Pattern and mould fabrication	43
3.4 Melting	46
3.4.1 Base iron preparation	46
3.5 Melting and casting	46
3.5.1 Base iron preparation	46
3.5.2 Alloying	47
3.6 Inoculation	48

3.7	Thermal analysis	50
3.8	Heat treatment process	51
3.9	Spectrometer analysis	52
3.10	Microstructure analysis	52
3.11	Mechanical testing	53
3.11.1	Hardness test	53
3.11.2	Tensile test	53
3.11.3	X-Ray Diffraction (XRD)	54
CHAPTER 4 RESULTS AND DISCUSSION		55
4.1	As-cast Experiment of Mn Ni-resist	55
4.1.1	Mechanical properties	55
4.1.2	Microstructure properties	57
4.1.3	Microhardness Test	62
4.1.4	SEM Analysis	64
4.1.5	XRD Analysis	67
4.1.6	Relationship of thermal analysis, mechanical properties, and microstructure	68
4.1.7	Effect of manganese on dendrite	73
4.2	Annealing	77
4.2.1	The effect of annealing on microstructure	77
4.2.2	The effect of annealing on dendrite shape	81
4.2.3	The effect of annealing on carbide size/area	83
4.2.4	The effect of annealing on strength	85
4.2.5	The effect of annealing on properties (Hardness)	87
4.2.6	Relationship of properties and macro hardness	88

CHAPTER 5 CONCLUSION	90
5.1 Conclusion	90
5.2 Limitation of Study	7
5.3 Further Improvement	91
REFERENCES	92
APPENDIX A	92
APPENDIX B	105

LIST OF TABLES

Table 2.1	Mechanical properties of 4 types of cast iron	12
Table 2.2	Chemical composition of Austenitic ductile iron	15
Table 3.1	Casting mold preparation	45
Table 3.2	Chemical composition of Pig Iron	46
Table 3.3	Element constituent in raw material	48
Table 4.1	Tensile properties of as-cast high manganese austenitic cast iron	56
Table 4.2	Element constituent in the microstructure	65
Table 4.3	Comparison of dendrite structure parameter based on Mn wt. % addition of alloyed iron	76
Table 4.4	Quantitative microstructure analysis	83
Table 4.5	Mechanical properties of high manganese austenitic cast iron	86

LIST OF FIGURES

Figure 2.1	Research tree	8
Figure 2.2	The iron–carbon phase diagram with composition ranges for commercial cast irons.	10
Figure 2.3	Microstructure of (a) White iron, (b) Gray Iron, (c) Malleable iron and (d) Ductile iron at 200 times magnification	12
Figure 2.4	Typical microstructure of Ni-resist (a) Gray Ni-resist (b) Ductile Ni-resist	14
Figure 2.5	Typical time-temperature-transformation curve (T-T-T) for cast iron.	17
Figure 2.6	Isothermal transformation diagram of austenite in cast iron. a) Without nickel; b) with 3.15% Ni; c) with 6.25% Ni	19
Figure 2.7	Effect of nickel on the microstructure of Ni-resist (a) with 4.99wt % (b) with 9.09 wt %Ni (c) with 13.5 wt%Ni (d) with 16.10wt%Ni	20
Figure 2.8	Iron- nickel equilibrium phase diagram	21
Figure 2.9	Three iron dendrites growing vertically into the liquid during solidification	23
Figure 2.10	Examples of structures in uninoculated and inoculated	25
Figure 2.11	Cooling curve (a) without chill formation (b) with chill formation	26
Figure 2.12	Fading of inoculation effect on eutectic cell counts in gray iron. 1. FeSi with Ba and Ca 2. FeSi with Sr and low Al 3. FeSi regular foundry-grade.	27
Figure 2.13	Austenitic promoter element	29
Figure 2.14	Iron- Manganese equilibrium phase diagram	30
Figure 2.15	Schematic of cooling curve temperature point	34
Figure 2.16	Definition of characteristic points on a solidification mode. Hypoeutectic (left) and a eutectic (right) cooling curve.	35
Figure 2.17	Typical cooling curve and its first derivative	36
Figure 3.1	Experiment flow chart	43
Figure 3.2	Y-block casting specification. The dimensions are in mm	44
Figure 3.3	Pattern was fabricated according to ASTM standard (a) upper side of the pattern (b) below side of the pattern	45
Figure 3.4	Casting Mould	45
Figure 3.5	Material preparation for treatment a) Fast Mills Machine b) Material container during milling process	49
Figure 3.6	Treatment material a) Ferro silicon b) Magnesium Ferro Silicon	49
Figure 3.7	Location of nodulant and inoculant in the mold	50

Figure 3.8	Schematic diagram of temperature monitoring during cooling	50
Figure 3.9	Heat treatment operation flow	51
Figure 3.10	Tensile test specimen (measurement in mm)	53
Figure 4.1	Tensile strength and macro-hardness graph	57
Figure 4.2	Pre-post process microstructure of AI-9 sample (a) microstructure with 100X magnification (b) carbide with 250X magnification (c) fracture morphology with 300X magnification (d) austenite morphology (deep etch) with 600X magnification.	59
Figure 4.3	Elements mapping showing micro-segregation behavior of the Mn-Ni-resist	61
Figure 4.4	Microhardness values in the microstructure.	63
Figure 4.5	Micro-hardness of carbidic region between graphite.	64
Figure 4.6	The microstructure of high manganese austenitic cast iron with carbide presence.	65
Figure 4.7	Element distribution at carbide formation	66
Figure 4.8	Point location to examine element distribution approximate to flake graphite structure.	67
Figure 4.9	Element distribution at flake graphite	67
Figure 4.10	Typical effect of manganese on AI-9 XRD phase pattern.	68
Figure 4.11	Determination of thermal arrest of TAL, TES, TEU, TER, TEE	69
Figure 4.12	Effect of Mn wt. % on solidification cooling curves (b) comparison of temperature points for addition of Mn from 9 to 12 wt. %	70
Figure 4.13	Temperature detail based on TAL, TES, TEU, TER and TEE position	73
Figure 4.14	Macrograph of alloyed iron macro structure after solidification showing graphite, dendrite arm spacing, and carbide distribution	74
Figure 4.15	Micrograph showing better resolution of alloyed iron structure after solidification showing graphite and dendrite arm spacing distribution	75
Figure 4.16	Micrograph showing close up of alloyed iron structure after solidification showing graphite and dendrite arm spacing distribution	75
Figure 4.17	Measurement of alloyed iron dendritic structure	76
Figure 4.18	Microstructure of the modified M-N-resist under 10X magnification: (a) As- cast condition, (c) Annealing 700°C, (e) Annealing 800°C (g) Annealing 900°C (i) Annealing 1000°C. With image analysis on carbide (b)(d)(f)(h)(j)	79
Figure 4.19	Comparison of alloyed iron (a) before annealing process and (b) after annealing process using picral etchant. The flake graphite and carbide distribution were dispersed and dissolved whenever annealing process takes effect	80

Figure 4.20	Macrograph of alloyed iron macro structure after annealing below 1000°C	81
Figure 4.21	Micrograph of alloyed iron microstructure showing transformation of graphite structure from flake to a finer mesh (without any recognized structure) after annealing 900°C	82
Figure 4.22	Higher magnification micrograph of alloyed iron microstructure showing the transformation of graphite structure from flake to a finer mesh at 1000°C. The austenitic structure was also reshuffled from common dendrite form to an unsymmetrical shape	82
Figure 4.23	Graph for carbide distribution according to a percentage, average single carbide form and overall carbide area in the microstructure	85
Figure 4.24	Comparison of tensile properties : (a) ultimate tensile strength, (b) elongation	86
Figure 4.25	Macro-hardness of the alloyed iron	87
Figure 4.26	Relationship between the tensile strength and macro hardness	88

LIST OF SYMBOLS

γ	Austenitic
α	Ferrite Iron
T_{liq}	Liquidus temperature
T_{und}	Undercooling temperature
T_{eut}	Eutectic temperature
T_{end}	End of solidification temperature
dT / dt	1st derivation
T_L	Austenite liquidus temperature
T_E	Equilibrium point of graphite eutectic temperature
T_C	Equilibrium point of carbide eutectic temperature
V	Volume
P	Density
C_p	Heat capacity
Q_L	Heat of solidification
T	Time
H	Convection heat transfer coefficient
A	Area
T	Temperature
D	Diffusion rate of carbon in austenite
R	Nodule size of graphite
S	Distance
X	Molar fraction
K_s	Segregation Coefficient

LIST OF ABBREVIATIONS

T-T-T	Time –temperature-transformation
ASTM	American standard for testing material
ADI	Austempered ductile iron
Ni-resist	Austenitic cast iron
TA	Thermal analysis
DNR	Ductile ni-resist
FCC	Face centered cubic
BCC	Body centered cubic
TAL	Temperature of the liquidus arrest
TES	Temperature of eutectic nucleation
TEU	Temperature of eutectic undercooling
TER	Temperature of eutectic recalescence
TEE	Temperature of the end of eutectic solidification
DTA	Differential thermal analysis
LTF	Last to freeze
DAS	Dendrite arm spacing
SDAS	Secondary dendrite arm spacing
TC	Total carbon
CEV	Carbon equivalent
CAE	Calculation of liquidus value
NiFe	Nickel Ferro
FeMn	Ferromanganese
MgFeSi	Magnesium ferrosilicon
FeSi	Ferrosilicon
SEM	Scanning electron microscopy
EDX	Energy dispersive X-ray spectroscopy
OM	Optical microscope
XRD	X-ray diffraction
kW	Kilowatt
HCL	Hydrochloric
KOH	Kalium hydroxide
NaOH	Natrium hydroxide
HMV	Hardness micro Vickers
HV	Hardness Vickers

REFERENCES

- 436, A. A. (2001). Standard Specification for Austenitic Gray Iron Castings. *ASTM International: Annual Book of ASTM Standards, iron and steel products*.
- A128, A. (2001). Standard Specification for Steel Castings, Austenitic Manganese. *ASTM International: Annual Book of ASTM Standards, 1*.
- A247, A. (2001). Standard Test Method for Evaluating the Microstructure of Graphite in Iron Castings. *ASTM International: Annual Book of ASTM Standards*.
- A439, A. (2001). Standard Specification for Austenitic Ductile Cast Iron Casting. *ASTM International: Annual Book of ASTM Standards, iron and steel products*.
- A644, A. (2003). Standard Terminology Relating to Iron Castings. *Annual Book of ASTM Standard, 1*(Reapproved), 70. doi:10.1016/S0016-0032(35)90652-4
- A. Janus, & K. Granat. (2014). Heat treatment of Ni–Mn–Cu cast iron. *Archives of Civil and Mechanical Engineering*, 14(4), 602-607. doi:10.1016/j.acme.2014.02.006
- A. Janus, & M. Stachowicz. (2014). Thermodynamic Stability of Austenite NI-Mn-Cu Iron. *Metallurgija*(53), 353 - 356.
- Ahmadabadi, M. N., Niyama, E., Tanino, M., Abe, T., & Ohide, T. (1994). Chemical composition and structural identification of eutectic carbide in 1 pct Mn ductile iron. *Metallurgical and Materials Transactions A*, 25(5), 911-918. doi:10.1007/bf02652266
- Alabbasian, F., Boutorabi, S. M. A., & Kheirandish, S. (2016). Effect of inoculation and casting modulus on the microstructure and mechanical properties of ductile Ni-resist cast iron. *Materials Science and Engineering: A*, 651, 467-473. doi:10.1016/j.msea.2015.09.024

- Alzafin, Y. A., Mourad, A. H. I., Zour, M. A., & Abuzeid, O. A. (2009). Stress corrosion cracking of Ni-resist ductile iron used in manufacturing brine circulating pumps of desalination plants. *Engineering Failure Analysis*, 16(3), 733-739. doi:<http://dx.doi.org/10.1016/j.engfailanal.2008.06.013>
- Aptekar', L. I., & Abramenko, Y. E. (1977). Structure and properties of austenitic nickel cast irons. *Metal Science and Heat Treatment*, 19(4), 280-292. doi:10.1007/bf00700810
- Asenjo, I., Larranaga, P., Sertucha, J., Suárez, R., Gómez, J. M., Ferrer, I., & Lacaze, J. (2007). Effect of mould inoculation on formation of chunky graphite in heavy section spheroidal graphite cast iron parts. *International Journal of Cast Metals Research*, 20(6), 319-324. doi:10.1179/136404608x286138
- Barton, R. (1958). Constitution, production and mechanical properties of Ni-Resist. *B.C.I.R.A. Journal of Research and Developmenmt*, 7, 299-308.
- Bhadeshia, H. K. D. H. (2002). Thermal analyses techniques. Differential thermal analysis. *University of Cambridge, Material Science and Metallurgy*.
- Boudot, A., Gerval, V., Oquab, D., Lacaze, J., & Santos, H. (1997). The role of manganese and copper in the eutectoid transformation of spheroidal graphite cast iron. *Metallurgical and Materials Transactions A*, 28(10), 2015-2025. doi:10.1007/s11661-997-0158-7
- Cabanne, P.-M. (2006). Thermal analysis: A useful technique for the foundryman. *Sorelmetal Technical Services*(103), 1-4.
- Calister, W. D., & Rethwisch, D. G. (2010). *Materials Science And Engineering - An Introduction* (8TH EDITION ed.): John Wiley & Sons, Inc.

- Chisamera, M., Riposan, I., & Liliac, M. (1995). High Active Inoculant Ferroalloy To Control Graphite Morphology And Nucleation Ability In Cast Iron. *INFACON7, Publishers: FFF, Trondheim, Norway*, 743 - 749.
- Chisamera, M., Riposan, I., Stan, S., Stefan, E., & Costache, G. (2009). Thermal analysis control of in-mould and ladle inoculated grey cast irons. *China Foundry*, 6(2), 145-151.
- Chisamera, M., Stan, S., Riposan, I., Costache, G., & Barstow, M. (2008). Solidification Pattern of In-Mold and Ladle Inoculated Low Sulfur Hypoeutectic Gray Cast Irons. *Buletinul Institutului Politehnic Din Iasi*, 4(8), 41 - 56.
- Covert, R. (1998). Properties and Applications of Ni Resist and Ductile Ni Resist Alloys. [https://nickelinstitute.org\(11018\)](https://nickelinstitute.org(11018)).
- Cox, G. J. (1988). Properties of alloy austenitic iron. *The Foundryman*, 81(Part 9), 453 - 443.
- Dasgupta, R. K., Mondal, D. K., Chakrabarti, A. K., & Ganguli, A. C. (2012). Kinetics of austenitisation of ductile irons containing two different contents of manganese and copper. *International Journal of Cast Metals Research*, 25(4), 239-245. doi:10.1179/1743133611Y.0000000022
- Davis, J. R. (1996). *Cast Irons* (J. R. Davis Ed.): ASM International.
- Dorazil, E. (1991). *High strength austempered ductile cast iron*: Ellis Horwood.
- E8/E8M, A. (2001). Standard Test Methods for Tension Testing for Metallic Materials. *ASTM International: Annual Book of ASTM Standards, 03.01 : Mechanical Testing, Elevated and Low-Temperature Tests, Metallography*. doi:10.1520/e0008_e0008m-09

- ELKEM. (2004). Technical Information 2 - Inoculation of Cast Iron. from Elkem ASA, Foundry Products
- ELKEM. (2012). Cast Iron - Inoculation.
- Elliott, R. (1988). Solidification Of Cast Iron *Cast Iron Technology*. London: Butterworth-Heinemann.
- Emadi, D., Whiting, V. L., Nafisi, S., & Ghomashchi, R. (2005). Applications of thermal analysis in quality control of solidification processes. *Journal of Thermal Analysis and Calorimetry*, 81(1), 235-242. doi:10.1007/s10973-005-0772-9
- Fallon, M. (1993). Heat and corrosion resistant of austenitic ductile iron. *BCIRA Technology*(9315), 8–14.
- Farahany, S., Ourdjini, A., & Idris, M. H. (2012). The usage of computer-aided cooling curve thermal analysis to optimise eutectic refiner and modifier in Al–Si alloys. *Journal of Thermal Analysis and Calorimetry*, 109(1), 105-111. doi:10.1007/s10973-011-1708-1
- Fatahalla, N., AbuElEzz, A., & Semeida, M. (2009). C, Si and Ni as alloying elements to vary carbon equivalent of austenitic ductile cast iron: Microstructure and mechanical properties. *Materials Science and Engineering: A*, 504(1-2), 81-89. doi:10.1016/j.msea.2008.10.019
- Forrest, R. D. (1983). Austenitic ductile iron. *foundry trade journal international*, 5(18), 138 - 142.
- Gagne, M., & Labreque, C. (2007). Effect of Wall Thickness on Graphite Morphology and Properties of D5-S Austenitic Ductile Iron. *AFS Transactions*, 115(Paper 07-004(05)).

- Geoffrey, S. (2014). Understanding Segregation to Predict Solidification *Modern Casting*, 104, 35 - 38.
- Giacopini, A., Boeri, R. E., & Sikora, J. A. (2013). Carbide dissolution in thin wall ductile iron. *Materials Science and Technology*, 19(12), 1755-1760. doi:10.1179/026708303225009445
- Glicksman, M. E. (2011). Microsegregation *Principles of Solidification: An Introduction to Modern Casting and Crystal Growth Concepts* (pp. 345-368). New York, NY: Springer New York.
- Gundlach, R., Meyer, M., & Winardi, L. (2015). Influence of Mn and S on the Properties of Cast Iron Part III—Testing and Analysis. *International Journal of Metalcasting*, 9(2), 69-82. doi:10.1007/bf03355617
- Harding, R. (1986). *Prospects for the Exploitation of ADI*. Paper presented at the 2nd International Conference on Austempered Ductile Iron, Ann Arbor, Michigan.
- Hasse Fredriksson, & Ulla A ° kerlind. (2006). Materials Processing during Casting *Microsegregation in Alloy— Peritectic Reactions and Transformations*. England: John Wiley & Sons.
- Hayrynen, K. L. (2002). The Production of Austempered Ductile Iron (ADI). *2002 World Conference on ADI*.
- Henderieckx, I. G. (2008). Ductile Iron - solidification mechanism. *Gietech BV Technical Information*.
- Hoskin, M. A. (1962). Critical Problems in the History of Science: Proceedings of the Institute for the History of Science at the University of Wisconsin, September 1-11, 1957. Marshall Clagett. *Isis*, 53(2), 230-231. doi:doi:10.1086/349553

- I. Riposan, M. Chisamera, S. Stan, & D. White. (2009). Complex (Mn, X)S compounds - major sites for graphite nucleation in grey cast iron. *China Foundry*, 6(4), 352 - 357.
- Jagmohan Datt, U. B. (2013). Influence of Composition and Austempering Temperature on Machinability of Austempered Ductile Iron. *International Scholarly and Scientific Research & Innovation*, 7(2), 116-121.
- Janus, A., & Kurzawa, A. (2013). Effect of Nickel Equivalent on Austenite Transition Ratio in Ni-Mn-Cu Cast Iron. *Archives of foundry engineering, Volume 13*(Issue 2/2013), 53–58.
- Jenkins, L. R., & Forrest, R. D. (1993). Ductile Iron (10th editi ed., pp. 64).
- Jiyang, Z. (2009a). Colour Metallography of Cast Iron - Grey Iron (III). *China Foundry*, 6(4), 366-374.
- Jiyang, Z. (2009b). Colour Metallurgy of Cast Iron - Introduction *China Foundry*. China: China Foundry.
- Johansson, M. (1977). Austenitic-Bainitic Ductile Iron. *Trans. AFS*, Vol 85, 117-122.
- Jolley, G., & Gilbert, G. N. J. (1967). Segregation in Nodular Iron and its Influence on Mechanical Properties. *The British Foundryman*(3), 72–92.
- Kalinina, L. T., Mayurnikov, A. V., Porublev, N. I., & Mayurnikov, V. V. (1975). Effect of copper on isothermal decomposition of austenite in silicon-manganese cast iron. *Metal Science and Heat Treatment*, 17(1), 87-88. doi:10.1007/bf00663102

- Lyadskii, V. B. (1963). Wear resistance of austenitic manganese cast iron in the case of friction between unlubricated cast irons. *Metal Science and Heat Treatment*, 5(11), 656-658. doi:10.1007/bf00660559
- Lyadskii, V. B., Mairansaev, M. U., & Teshaev, S. T. (1967). Effect of Annealing On the Hardness and Resistance to Abrasive Wear of Austenitic Manganese Cast Iron. *Tadzhik Agricultural Institute. Translated from Metallovedenie Termicheskaya Obrabotka Metallov*(8), 57 - 58.
- Mampaey, F. (2002). Solidification Mode and Feeding Behavior of Austenitic Cast Iron. *AFS Transactions*, 2(24), 1 - 20
- McKay, & Robert, J. (1936). Nickel and corrosion-resisting nickel alloys. *Industrial and Engineering Chemistry*, 28(12), 1391-1397. doi:10.1021/ie50324a012
- Morrison, J. C. (1998). Practical production of Ni-resist castings. *Foundry Manage Technology*, 126, 54–64.
- Murthy, K. N., Sampathkumaran, P., & Seetharamu, S. (2009). Abrasion and erosion behaviour of manganese alloyed permanent moulded austempered ductile iron. *Wear*, 267(9-10), 1393-1398. doi:10.1016/j.wear.2008.12.033
- Nili-Ahmadabadi, M., & Feghahati, S. (2013). Use of modelling to optimise homogenisation of high Mn heavy section ductile iron castings using partial melting. *International Journal of Cast Metals Research*, 20(2), 53-57. doi:10.1179/136404607x239708
- Olsen, S. O., Skaland, T., & Hartung, C. (2005). *Inoculation of Grey and Ductile Iron - A Comparison Of Nucleation Sites and Some Practical Advises*. Paper presented at the 14th International Baltic Conference Materials Engineering.

- Oshima, T. (2007). Efforts to Save Nickel in Austenitic Stainless Steels. *ISIJ International*, 47(3), 359–364.
- Owhadi, A., Hedjazi, J., Davami, P., Fazli, M., & Shabestari, J. M. (1997). Microsegregation of manganese and silicon in high manganese ductile iron. *Materials Science and Technology*, 13(10), 813-817. doi:10.1179/mst.1997.13.10.813
- Ozaki, R., Okada, A., & Miyake, H. (1968). Influences of Carbon, Silicon, Manganese and Sulfur on the Eutectic Cell Number in Gray Cast Iron. *THE JOURNAL OF THE JAPAN FOUNDRYMEN'S SOCIETY*, 40(1), 26-36. doi:10.11279/imon.40.1_26
- Park, G.-D., Heo, H.-J., Na, H.-S., & Kang, C.-Y. (2012). Effect of the Cu Composition Ratio on the Phase Transformation in Low Ni Austenite Cast Iron, Fe-3%C-16%(Ni+Mn+Cu). *Journal of Korean Institute of Metals and Materials*, 50 (6), 419-425. doi:10.3365/KJMM.2012.50.6.419
- Paulik, F., Paulik, J., & Erdey, L. (1966). Derivatography. *Talanta*, 13(10), 1405-1430. doi:[http://dx.doi.org/10.1016/0039-9140\(66\)80083-8](http://dx.doi.org/10.1016/0039-9140(66)80083-8)
- Pearce, J. (2008). Inoculation of cast irons practice and developments. *foundry trade journal international*, 28 - 32.
- Popovski, V. (2004). Determining the Optimum Level of Inoculant Addition by Thermal Analysis – A Case Study. *ELKEM ASA Research*, 1 - 8.
- Popovski, V., Misterek, C., & Kaiser, L. (2005). *Metallurgical Comparisons Operating Conditions, Inoculant Types and Fade Effects In Gray Iron*. Paper presented at the AFS Cast Iron Inoculation Conference, Schaumburg, Illinois.

- Poyet, P., Couchinave, P., & Dancoisne, P. I. (1984). Effects of Nickel substitution by Manganese in Austenitic S.G. Cast Iron for Low-Temperature Uses. *MRS Online Proceedings Library Archive*, 34, 345 (349 pages). doi:doi:10.1557/PROC-34-345
- Putatunda, S. K. (2003). Influence of austempering temperature on microstructure and fracture toughness of a high-carbon, high-silicon and high-manganese cast steel. *Materials & Design*, 24(6), 435-443. doi:[http://dx.doi.org/10.1016/S0261-3069\(03\)00090-6](http://dx.doi.org/10.1016/S0261-3069(03)00090-6)
- Rashidi, M. M. (2014). *Manganese As Austenitic Matrix Stabilizer For Ductile Ni-resist Alloy Using In-mould Magnesium Treatment Method*. (philosophy Degree), University Technology Malaysia.
- Rashidi, M. M., & Hasbullah, I. M. (2013). Effect of inoculation on microstructure, mechanical and corrosion properties of high manganese ductile Ni-resist alloy. *Materials & Design*, 51, 861-869. doi:10.1016/j.matdes.2013.04.064
- Rashidi, M. M., & Hasbullah, I. M. (2014). The effects of solidification on the microstructure and mechanical properties of modified ductile Ni-resist iron with a high manganese content. *Materials Science and Engineering: A*, 597, 395-407. doi:10.1016/j.msea.2013.12.070
- Rashidi, M. M., Hasbullah, I. M., & Shayfull, Z. (2013). The Effect of Inoculation on Properties of Modified Ductile Ni-Resist Alloy. *Key Engineering Materials*, 594-595, 98-112. doi:10.4028/www.scientific.net/KEM.594-595.98
- Rashidi, M. M., & M. Hasbullah, I. (2013). Microstructure and mechanical properties of modified ductile Ni-resist with higher manganese content. *Materials Science and Engineering: A*, 574, 226-234. doi:10.1016/j.msea.2013.02.038

- Roula, A., & Kosnikov, G. A. (2008). Manganese distribution and effect on graphite shape in advanced cast irons. *Materials Letters*, 62(23), 3796-3799. doi:10.1016/j.matlet.2008.04.056
- S.C.Borse, Y. E. M. (2014). Review on Grey Cast Iron Inoculation. *International Journal of Innovative Research in Science, Engineering and Technology*, 3(4), 30 - 36.
- Seidu, S. O., Owoeye, S. S., & Owoyemi, H. T. (2015). Assessing the effect of copper additions on the corrosion behaviour of grey cast iron. *Leonardo Electronic Journal of Practices and Technologies*(26), 49-58.
- Sertucha, J., Larrañaga, P., Lacaze, J., & Insausti, M. (2010). Experimental Investigation on the Effect of Copper Upon Eutectoid Transformation of As-Cast and Austenitized Spheroidal Graphite Cast Iron. *International Journal of Metalcasting*, 4(1), 51-58. doi:10.1007/bf03355486
- Shebatinov, M. P., & Abramenko, Y. E. (1986). Properties and wear resistance of austenitic cast iron. *Metal Science and Heat Treatment*, 28(6), 425 - 431. doi:10.1007/BF00836891
- Skaland, T. (1999). Ductile Iron Production - A Comparison of Alternative Treatment Methods. *ELKEM ASA Research*, 1 - 19.
- Sparkman, D. A. (2010). Thermal Analysis Metrics by Derivatives.
- Stanchev, D. I., Rublev, V. I., Sednev, Y. G., & Filatov, A. M. (1976). Effect of heat treatment on structure and properties of manganese cast iron. *Metal Science and Heat Treatment*, 18(6), 514-516. doi:10.1007/bf00774934
- Stefanescu, D. M. (1993). Ferrous Casting Alloy *ASM handbook*, Vol. 15 - Casting (Vol. Vol. 15, pp. 1362 - 1615): ASM International.

- Stefanescu, D. M. (2005). Solidification and modeling of cast iron—A short history of the defining moments. *Materials Science and Engineering: A*, 413-414, 322-333. doi:10.1016/j.msea.2005.08.180
- Stefanescu, D. M. (2015). Thermal Analysis—Theory and Applications in Metalcasting. *International Journal of Metalcasting*, 9(1), 7-22. doi:10.1007/bf03355598
- Verhoeven, J. D. (2007). Solidification *Steel Metallurgy for the Non-Metallurgist* (pp. 165-174): ASM International.
- Volkov, A. N. (1974). Stability of austenite in steel G13L and cast irons with manganese. *Metal Science and Heat Treatment*, 16(2), 173-175. doi:10.1007/bf00649803
- Volkov, A. N., Lyadskii, V. B., & Stanehev, D. I. (1968). *Effect of Heat Treatment on the Wear Resistance of Manganese Cast Irons*. Metallovedenie i Termicheskaya Obrabotka Metallov, (5).
- Walton, C. F. (1993). ASM Handbook-Vol 4 - Heat treating *Heat treating* (10th Edition., Vol. 4, pp. 1451 - 1516): ASM International.
- Warda, R. (1998). Ductile Iron Data For Engineers. <http://www.ductile.org/>.
- Yaer, X., Shimizu, K., Matsumoto, H., Kitsudo, T., & Momono, T. (2008). Erosive wear characteristics of spheroidal carbides cast iron. *Wear*, 264(11-12), 947-957. doi:10.1016/j.wear.2007.07.002
- Yang, Y. L., Cao, Z. Y., Lian, Z. S., & Yu, H. X. (2011). A Study on Microstructure of Ductile Ni-Resist Cast Iron for Exhaust Manifolds and Mechanical Property at the Condition of Alternative Thermal Cycles. *Advanced Materials Research*, 194-196, 95-99. doi:10.4028/www.scientific.net/AMR.194-196.95

- Yatsenko, A. I., & Martsiniv, B. F. (1968). Effect of nickel on the transformation of austenite in gray cast iron. *Metal Science and Heat Treatment*, 10(11), 890-894. doi:10.1007/bf00649218
- Zeng, D., Xie, C., Hu, Q., & Yung, K. C. (2001). Corrosion resistance enhancement of Ni-resist ductile iron by laser surface alloying. *Scripta Materialia*, 44(4), 651-657. doi:[http://dx.doi.org/10.1016/S1359-6462\(00\)00620-5](http://dx.doi.org/10.1016/S1359-6462(00)00620-5)
- Zhang, L., Du, Y., Xu, H., Liu, S., Liu, Y., Zheng, F., . . . Tang, C. (2009). Phase equilibria and thermal analysis in the Fe–Mn–Ni system. *International Journal of Materials Research*, 100(2), 160-175. doi:10.3139/146.110002